

## 10/100 Mbps MM Fiber Ethernet Managed Media Converter ST

MMC110MMST



\*actual product may vary from photos

DE: Bedienungsanleitung - [de.startech.com](http://de.startech.com)

FR: Guide de l'utilisateur - [fr.startech.com](http://fr.startech.com)

ES: Guía del usuario - [es.startech.com](http://es.startech.com)

IT: Guida per l'uso - [it.startech.com](http://it.startech.com)

NL: Gebruiksaanwijzing - [nl.startech.com](http://nl.startech.com)

PT: Guia do usuário - [pt.startech.com](http://pt.startech.com)

For the most up-to-date information, please visit: [www.startech.com](http://www.startech.com)

## FCC Compliance Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

## Use of Trademarks, Registered Trademarks, and other Protected Names and Symbols

This manual may make reference to trademarks, registered trademarks, and other protected names and/or symbols of third-party companies not related in any way to StarTech.com. Where they occur these references are for illustrative purposes only and do not represent an endorsement of a product or service by StarTech.com, or an endorsement of the product(s) to which this manual applies by the third-party company in question. Regardless of any direct acknowledgement elsewhere in the body of this document, StarTech.com hereby acknowledges that all trademarks, registered trademarks, service marks, and other protected names and/or symbols contained in this manual and related documents are the property of their respective holders.

# Table of Contents

<b>Introduction .....</b>	<b>1</b>
Features .....	1
Package Contents .....	1
<b>Installation .....</b>	<b>2</b>
Connecting to Power .....	2
<b>Configuration and Management .....</b>	<b>3</b>
Web Browser Configuration .....	3
Telnet Management .....	12
<b>LED Status Indicators .....</b>	<b>13</b>
<b>Specifications .....</b>	<b>14</b>
<b>Technical Support .....</b>	<b>15</b>
<b>Warranty Information .....</b>	<b>15</b>

# Introduction

Thank you for purchasing a StarTech.com Managed 10/100 Mbps RJ45 to Multimode ST Fiber Media Converter. A perfect solution for large, high speed networks that require expansion of fast Ethernet networks over long distances, the MMC110MMST acts as a standalone device allowing for one-channel media conversion between 10/100 Base-TX and 100 Base-FX network segments.

Featuring fully integrated managed software, and support for Telnet, SNMP v1 and v2 and Web Browser management, the MMC110MMST ensures broad compatibility and maximum installation and configuration convenience.

## Features

- 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- 1024 MAC addresses
- 256Kbps of buffer memory
- Compact design and weight makes it portable and unobtrusive to carry
- LED Indicators that detect Power, Link, Activity, Duplex mode, and Collision status
- Provides MAC address filtering
- Supports Telnet, SNMP V1 & V2 and Web Browser Management

## Package Contents

- 1 x MMC110MMST
- 1 x Information CD
- Universal Power Adapter

# Installation

For optimal performance and safety, ensure that the MMC110MMS is installed in an area that meets the following specifications:

- A temperature between 0 to 45° Celsius (32° and 113° Fahrenheit)
- Relative Humidity (RH) less than 95% (non condensing)
- Surrounding electrical devices that do not exceed the electromagnetic field (RFC) standards for IEC 801 3, Level 2 (3V/M) field strength
- Adequate ventilation, with the ventilation holes on each side of the equipment being clear of obstruction
- Power outlet within 1.8 meters (5.9') of the product

## Connecting to Power

Connect the AC to DC power adapter to the receptacle on the rear panel of the MMC110MMS, then insert the corresponding plug into a standard AC outlet with a voltage range from 100 to 240VAC.

**PLEASE NOTE:** A grounding strap should be worn while handling the Media Converter as well as when plugging and unplugging the TX port connector.

# Configuration and Management

The MMC110MMST Media Converter can be configured and managed through SNMP, Web browsers, and Telnet, as outlined in the following sections:

## Web Browser Configuration

### Logging Into The Monitoring System

The MMC110MMS is accessible through a web browser such as Internet Explorer. To access the MMC110MMS monitoring system, enter the default IP address of the MMC110MMS, 192.168.1.10, into your browser's address bar. By default, the username and password to access the monitoring system are set to blank fields. The password can be changed once the user has logged in; the username is not required to log into the monitoring system and can be left blank.

### Logging Out Of The Monitoring System

The MMC110MMS monitoring system does not include a separate log out function. The system automatically ends a management session when the browser software is closed. Logging off by closing the browser and then logging in again may be required if changes made during a management session do not seem to take effect on-screen.

## Main Menu


The main menu of the monitoring system is persistently displayed on the left side of the screen after log-in. Options can be selected with the mouse cursor. The sub-menus available from the main menu are:

- System Change
- IP Configuration
- MC Status
- MC Control
- MAC Address Filter
- VLAN Configuration
- SNMP Configuration
- Alarm
- Save
- Update Firmware
- Reboot

**NOTE:** The **Apply** button on each sub-menu page applies changes for that page, but **does not** save them beyond the current session. For any changes made, the user must select **Save** from the main menu.

## System Change Menu

The **System Change** menu contains the following fields that users can edit:



- **Device Name:** A device name for the MMC110MMS can be set by the user in this field.
- **New Password:** A new password for the monitoring system can be set in this field. Setting a new password in this field requires entering the previous password in the Old Password field.
- **Old Password:** The password that was previously being used to log in to the monitoring system must be entered here when a new password is being applied. If the password is being changed from the default blank field, this field should be left blank.


The **System Change** menu also contains two fields that display reference information:

- **Version:** The version of software currently being used.
- **MAC Address:** The MAC address assigned to the MMC110MMS.

**NOTE:** The **Apply** button in each sub-menu page applies changes for that page, but does not save them beyond the current session. For any changes made, the user must select "Save" from the main menu.

## IP Configuration

The **IP Configuration** sub-menu contains the following fields that can be set by the user:






- **DHCP:** Allows the user to set DHCP to “Enable” or “Disable”. If DHCP is enabled the MMC110MMS will set its IP address according to a DHCP server. This IP will replace any other IP address that the Media Converter had been using.
- **IP Address:** Allows the user to set an IP address for the MMC110MMS. The default address is 192.168.1.10.
- **Netmask:** Allows the user to set the Netmask or subnet mask. The default is 255.255.255.0.
- **Default Gateway:** Allows the user to set the gateway address of the MMC110MMS in the network. The default is 192.168.1.254.

**NOTE:** The **Apply** button in each sub-menu page applies changes for that page, but does not save them beyond the current session. For any changes made, the user must select “Save” from the main menu.

## MC Status

The **Media Converter Status** sub-menu contains the following reference fields for a user to view:

- **Operation Status:** Normal, Hardware Fault or Software Fault




- **Media Port Status:** Individual status reports for both the 10/100 TX port and 100 FX port in these categories:

- Link Status
- Receive Count
- CRC Count
- Drop Count
- Collision Count

**NOTE:** The **Apply** button in each sub-menu page applies changes for that page, but does not save them beyond the current session. For any changes made, the user must select “Save” from the main menu.

## MC Control

The **Media Converter Control** sub-menu contains three main categories of fields:



- **MC Options:**
  - **Forwarding Mode:** Can be set to either “Store & Forward” or “Repeater” mode.
  - **Broadcast Limit (%)**: Allows the user to set a percent

- age limit on how much bandwidth is allocated for broadcast traffic passing through the MMC110MMS. If Broadcast Storm Protection is enabled on either or both of the ports, the Broadcast Limit percentage will be applied on the data packets using that port.

#### • **Media Port 1: 10/100 TX**

- **Port Mode:** Allows the user to set the port mode to Auto, 10 Half Duplex (HD), 10 Full Duplex (FD), 100HD, or 100FD.
- **Flow Control:** Allows the user to enable or disable Flow Control. If Flow Control is enabled, the input and output rates are set in subsequent fields.
- **Broadcast Storm Protection:** Allows the user to enable or disable Broadcast Storm Protection, according to the parameters set in the Broadcast Limit (%) field.
- **Output Rate:** Allows the user to select the output rate for this port from the following options: Full, 6%, 12%, 18%, 24%, 30%, 36%, 42%, 48%, 54%, 60%, 66%, 72%, 78%, 84%, or 90%.
- **Input Rate:** Allows the user to select the input rate for this port from the following options: Full, 6%, 12%, 18%, 24%, 30%, 36%, 42%, 48%, 54%, 60%, 66%, 72%, 78%, 84%, or 90%.

#### **Media Port 2: 100 FX**

- **Port Mode:** Allows the user to set the port mode to Auto, 10HD, 10FD, 100HD, or 100FD.
- **Flow Control:** Allows the user to enable or disable Flow Control. If Flow Control is enabled, the input and output rates are set in subsequent fields.
- **Broadcast Storm Protection:** Allows the user to enable or disable Broadcast Storm Protection, according to the parameters set in the Broadcast Limit (%) field.


**NOTE:** The **Apply** button in each sub-menu page applies changes for that page, but does not save them beyond the current session. For any changes made, the user must select “Save” from the main menu.

## MAC Address Filter

The **MAC Address Filter** sub-menu contains fields for each of the two ports on the MMC110MMS that allows the user to enable MAC address filtering for specific addresses. If one or more MAC addresses are enabled, the filter process is turned on and only those MAC addresses that are enabled will be able to pass through the MMC110MMS. All packets with MAC addresses that are not listed will be blocked.

**NOTE:** The **Apply** button in each sub-menu page applies changes for that page, but does not save them beyond the current session. For any changes made, the user must select “Save” from the main menu.

## VLAN Configuration




The **VLAN Configuration** sub-menu has four main columns of fields:

- **Active:** Allows the user to enable VLAN configuration

- **VLAN ID:** Allows the user to enter a VLAN ID number.
- **VLAN Member:** Allows the user to configure which ports will be added to a VLAN group. Users can choose TX Port, FX Port, or Mgmt Port. If Mgmt Port is selected, one of TX Port or FX Port must also be selected.
- **Untag:** Allows the user to enable tagged or untagged VLAN for that VLAN group. The MMC110MMS supports a maximum of one untagged VLAN.

**NOTE:** The **Apply** button in each sub-menu page applies changes for that page, but does not save them beyond the current session. For any changes made, the user must select "Save" from the main menu.

## SNMP Configuration



The **Simple Network Management Protocol (SNMP)** Configuration sub-menu provides four fields for users to edit:

- **System Contact:** Allows the user to enter the name of the person in charge of the network system.
- **System Location:** Allows the user to set the location of the network system.

- **Get Community:** Allows the user to set the getcommunity string. If the system only knows the get community string, it can only read MIBs. The default get community string for the media converter is public.
- **Set Community:** Allows the user to set the setcommunity string. If the SNMP Network management station only knows the set community string, it can read and write to the MIBs. The default set community string for the media converter is public.

**NOTE:** The **Apply** button in each sub-menu page applies changes for that page, but does not save them beyond the current session. For any changes made, the user must select "Save" from the main menu.

## Alarm

The **Alarm** sub-menu allows a user to enable or disable alarms for the following scenarios:

- **MC Fault:** Alarm will be triggered if the internal communication of the Media Converter fails.
- **MC Link Status Changed:** Alarm will be triggered if the status of the link between two Media Converters changes.
- **System Reboot:** Alarm will sound if the MMC110MMS reboots.

The **Alarm** sub-menu allows the user to configure email alerts when an alarm is triggered. Options available here include:

- **Alarm by SMTP:** Allows the user to enable or disable email alerts.
- **SMTP Server Address:** Allows the user to set the IP address of the server that will send the email alert.
- **Mail From:** Allows the user to set the "From" email address.
- **Mail To:** Allows the user to set the email address that the email alerts will be sent to.
- **User Name:** Allows the user to enter the username of the SMTP server account.

**Password:** Allows the user to enter the password of the SMTP server account.

The **Alarm** sub-menu also allows the user to set SNMP traps for: MC Link-Status Changed System Reboot.

The user can choose **Trap Host V1** or **V2** and input IP addresses for four trap hosts.

**NOTE:** The **Apply** button in each sub-menu page applies changes for that page, but does not save them beyond the current session. For any changes made, the user must select “Save” from the main menu.

## Save

The **Save** sub-menu allows the user to confirm any changes that have been made in the monitoring system. If changes are not confirmed with this function, they will not be stored in the MMC110MMS.

## Update Firmware

The Update Firmware sub-menu allows the user to download new firmware for the MMC110MMS. There are two fields in this sub-menu:

- **TFTP Server IP Address:** Allows the user to enter the IP address of the server that the new firmware will be downloaded from.
- **File Name:** Allows the user to enter the file name of the firmware to be installed.

Once the information in the fields is correct, pressing the **Upgrade** button begins the installation. Pressing the **Reset** button will clear the fields.

## Reboot

The **Reboot** sub-menu allows the user to reboot the MMC110MMS. Rebooting through this menu will require a new log-in to the monitoring system after the MMC110MMS is successfully rebooted.


## Telnet Management

To begin managing the MMC110MMS through Telnet, log in to the Media Converter by entering your password; the username field is not required by the device. The following commands are available from the Main

## Screen:

- **Get Command** - Usage: get(g) <OPTION>
  - mc-status(ms).....Get central MC status
  - mc-config(mc).....Get central MC configuration
  - netconf(nc).....Get networking configuration
  - sysinfo(si).....Get system information
- **Set Command** - Usage: set(s) <OPTION>
  - mc-mode(mm).....Set central MC operation mode
  - port-mode(pm).....Set central MC port mode
  - port-rate(pr).....Set central MC port rate
  - netconf(nc).....Set networking configuration
  - sysadmin(sa).....Set system administrator

## LED Status Indicators



LED	State	Indication
1. PW/FA	Steady (Green)	Power On
	Off	Power Off
	Steady (Orange)	Booting or failed
2. LK/AT	Steady	Valid connection
	Flashing	Transmitting/receiving
	Off	No connection
3. FD/CL	Steady	Full duplex mode
	Flashing	Collision occurred
	Off	Half duplex mode



# Specifications

<b>Applicable Standards</b>	IEEE802.3 10Base-T IEEE802.3u 100Base-TX/100Base-FX
<b>Ports</b>	1-port 10/100Base-TX with RJ-45 connector 1-port 100Base-FX with fiber optic connector
<b>Speed</b>	100Base-TX: 200Mbps full duplex 100Mbps half duplex 10Base-T: 20Mbps full duplex 10Mbps half duplex
<b>Performance</b>	148,810pps forwarding rate for 100Mbps 14,880pps forwarding rate for 10Mbps
<b>Port LED Indicators</b>	Unit: PW/FA TX: LK/AT, FD/CL FX: LK/AT
<b>Dimensions</b>	80mm (W) x 145mm (D) x 20mm (H) (3.15" (W) x 5.71" (D) x 0.79" (H))
<b>Weight</b>	150g (0.33lb.)
<b>Power Input</b>	0.27A @ 12VDC
<b>Power Consumption</b>	3.24W Max
<b>Operating Temperature</b>	0°C ~ 45°C (32°F ~ 113°F)
<b>Storage Temperature</b>	-10°C ~ 70°C (14°F ~ 158°F)
<b>Humidity</b>	5~95%, non condensing
<b>Emissions</b>	FCC Part 15 Class A, CE Mark Class A

# Technical Support

StarTech.com's lifetime technical support is an integral part of our commitment to provide industry-leading solutions. If you ever need help with your product, visit **[www.startech.com/support](http://www.startech.com/support)** and access our comprehensive selection of online tools, documentation, and downloads.

For the latest drivers/software, please visit **[www.startech.com/downloads](http://www.startech.com/downloads)**

## Warranty Information

This product is backed by a two year warranty.

In addition, StarTech.com warrants its products against defects in materials and workmanship for the periods noted, following the initial date of purchase. During this period, the products may be returned for repair, or replacement with equivalent products at our discretion. The warranty covers parts and labor costs only. StarTech.com does not warrant its products from defects or damages arising from misuse, abuse, alteration, or normal wear and tear.

### Limitation of Liability

In no event shall the liability of StarTech.com Ltd. and StarTech.com USA LLP (or their officers, directors, employees or agents) for any damages (whether direct or indirect, special, punitive, incidental, consequential, or otherwise), loss of profits, loss of business, or any pecuniary loss, arising out of or related to the use of the product exceed the actual price paid for the product. Some states do not allow the exclusion or limitation of incidental or consequential damages. If such laws apply, the limitations or exclusions contained in this statement may not apply to you.

Hard-to-find made easy. At StarTech.com, that isn't a slogan. It's a promise.

StarTech.com is your one-stop source for every connectivity part you need. From the latest technology to legacy products — and all the parts that bridge the old and new — we can help you find the parts that connect your solutions.

We make it easy to locate the parts, and we quickly deliver them wherever they need to go. Just talk to one of our tech advisors or visit our website. You'll be connected to the products you need in no time.

Visit [www.startech.com](http://www.startech.com) for complete information on all StarTech.com products and to access exclusive resources and time-saving tools.

*StarTech.com is an ISO 9001 Registered manufacturer of connectivity and technology parts. StarTech.com was founded in 1985 and has operations in the United States, Canada, the United Kingdom and Taiwan servicing a worldwide market.*